

XEROX® PRIMELINK® PRINTER

The world's #1* entry production color printer just got even better.



C9065 AND C9070



Xerox® PrimeLink® C9065 and C9070 Printer

The Xerox® PrimeLink® C9065/C9070 delivers the most adaptable capabilities on the market. From superior image quality and unmatched media flexibility to professional-grade finishing, automation and security, it takes entry level to the next level.



IMPROVE YOUR IMAGE

Entry-level price point shouldn't mean entrylevel image quality. With PrimeLink, you can deliver stunning output on every job, every time.

It all starts with resolution. 2400 x 2400 dpi means you get outstanding fine-line detail and text with vivid images and smooth color transitions — even at speeds of up to 70 ppm. EFI servers with embedded PANTONE® technologies such as PANTONE® GOE and PANTONE® PLUS ensure the colors you want are the colors you get.

And a combination of Xerox® Emulsion Aggregation (EA) toner with ultra-low melt technology, +/- 1.2 mm front-to-back registration and Simple Image Quality Adjustment (SIQA) means you get consistent quality from your first print to your last.



^{*} Idealliance, Fogra, and Adobe PDF Print Engine achieved with the optional EFI server

WORK SMARTER, NOT HARDER

Looming deadlines are the norm. Now, there's no reason to compromise. Adding a PrimeLink to your arsenal lets you upgrade your productivity in ways you wouldn't think possible.

Designed to promote multitasking and collaboration, it's customizable to suit your work style. The Xerox® Integrated Color Server comes standard. Or you can choose from one of three optional EFI servers for more capabilities and more volume. All you have to do is select the best fit based on your business applications and the level of automation and color accuracy you need.

The printer also has access to the Xerox App Gallery. With apps that connect to leading applications including Box®, Microsoft® OneDrive®, Google Drive™, Dropbox™ and Microsoft Office 365™, you can print and scan directly to and from the cloud, simplify workflows and automate complex tasks.

Plus, built-in mobile connectivity with @printbyXerox lets your team stay on-task when they're on the go. With this feature, PrimeLink can securely accept print submissions from any email-enabled device — no extra software required.

It's all there with the touch of a button. Say yes to more, and Xerox® PrimeLink C9065/C9070 will help you deliver.

SERVE AND PROTECT

PrimeLink applies a strategic approach to security to keep your network and projects safe from prying eyes. Stop suspicious activity where it starts with our comprehensive approach to security:

- Multiple layers of security include data encryption, access controls, disk overwrite and industry certifications.
- Audit Log ensures an audit trail of operators' key events. These logs are imperative for Administrators/Key Operators to use for troubleshooting, resource optimization and security audits.
- Secure Print holds documents for release until you're ready to retrieve them.
- Secure Scanning includes password protection for PDFs and folders, as well as encryption for scanning to email.

FINISH STRONG

PrimeLink delivers media latitude and finishing options that are best-in-class and unparalleled in an entry-level device.

Print on specialty stocks and heavyweight stocks up to 350 gsm. Print up to 26" (660 mm) with the Extra Long Sheet (XLS) capability up to 220 gsm. And print long runs without refilling the paper tray using high volume feeding options.

Finishing options are professional-grade, easy to navigate and nearly endless. Enjoy options ranging from full-bleed trimmed booklets to punch, crease and fold.



Xerox® PrimeLink® C9065/C9070 Printer

- **1 Two-Tray Oversized High Capacity Feeder:** Adds 4,000 sheets in sizes from 7.2 x 10 in./182 x 250 mm (B5) (up to 350 gsm) to 13 x 26 in./330 x 660 mm (up to 220 gsm).
- 2 Extra Long Sheet (XLS) Capability: Print banners, book jackets, calendars and other applications up to 26 in. (660 mm) long, and up to 220 gsm.
- 3 Control Panel: An intuitive user interface makes it simple to access general print, copy, scan and fax functions, integrated color server, useful apps from the Xerox App Gallery, color controls, security features and much more.
- 4 Integrated Scanner: Single Pass Automatic Document Feeder scans up to 270 impressions per minute; 600 dots per inch color up to 11 x 17/A3. Scan to a variety of output options; desktop, USB, mailbox, FTP, SFTP, NDS, SMB and Job Flow multi-destination scanning.
- 5 Xerox® PrimeLink C9065/C9070 Printer: Prints, copies, scans and faxes all while delivering stunning color image quality at a highly productive 65 ppm color and 70 ppm black-and-white (C9065) or 70 ppm color and 75 ppm black-and-white (C9070).
- **6 Five Internal Trays (Standard):** Includes a 12 x 18 in./SRA3 tray and Tray 5 (Bypass) max weight up to 350 gsm and up to 26 in./ 660 mm sheet size.
- 7 Xerox® Interface Decurler Module: Inline paper cooling and decurler unit improves throughput and efficiency, connecting Production Ready finishing modules, ensuring flat sheets for reliability and speed.

- 8 Xerox Inserter: Insert preprinted or blank media into printed documents with a tray capacity of 250 sheets, sheet sizes up to 13.0 x 19.2 in. (330 x 488 mm) and 350 gsm.
- **9 GBC® AdvancedPunch Pro™:** Lets you create bound documents in-house by combining printing, punching and collating into one convenient step. Choose the punch to fit your needs.
- 10 Xerox® Crease and Two-sided Trimmer: Trims 6-25 mm from the head and foot of prints or booklets to produce an even edge and creases spine. Available on Production Ready Finishers.
- **11 Xerox® C/Z Folder:** Produces Z-fold, C-Fold and Engineering Z-Fold.
- 12 Xerox® Production Ready Finisher Booklet Maker: Ensures consistent high-quality stapled sets for small or large documents with a variable-length stapler, single or dual stapling option and a 100 sheet capacity. Plus, creates stapled booklets up to 30 sheets or 120 imposed pages (uncoated), or 15 sheets or 60 imposed pages (coated).
- 13 Xerox® SquareFold® Trimmer Module: Enhances the power of the Production Ready Finisher with square fold of cover sheets and face trimming to produce booklets.

ADDITIONAL FEEDING AND FINISHING OPTIONS NOT PICTURED

- One-Tray Xerox® High Capacity Feeder Holds 2,000 sheets of 8.5 x 11 in. (A4) paper, 64–220 gsm.
- Banner Feed Guide An option for the Tray 5 (Bypass)/MSI/OHCF that increases reliability when feeding XLS or 350 gsm media.
- One-Tray Oversized High Capacity Feeder with Storage Cabinet — Adds 2,000 sheets in sizes from 4 x 6 in. / 102 x 152 mm (up to 350 gsm) to 13 x 26 in. / 330 x 660 mm (up to 220 gsm).
- Offset Catch Tray 500-sheet stacking.
- Xerox® Business Ready Finisher A lighterduty option for finishing and stacking and staples up to 50 sheets uncoated/15 coated.
- Xerox® Business Ready Booklet Maker Finisher
 Provides booklet making capability.
- Xerox® Production Ready Finisher Produces superior quality finishing and stacking with a 500-sheet top tray and 2,000-sheet stacker tray and built-in bi-directional decurler.
- Xerox® Production Ready Finisher Plus —
 Provides same function as the Production
 Ready Finisher. Used to connect third-party
 inline finishing options.
- Xerox® Basic Punch An option for punching 2/3, 2/4 and Swedish 4-hole on the Production Ready Finisher and Booklet Maker.
- Plockmatic Pro 50/35 Booklet Maker Highest quality production booklets up to 200 pages (up to 50 sheets). Face trimming, square fold, rotate crease and bleed trim.
- Convenience Stapler Staples up to 50 sheets of 20 lb./80 gsm media.

FINISHING APPLICATIONS							
Sort and Collate	XLS	Tri-Fold	Square Fold	Face Trim	Hole Punch		
Booklet	Tabloid Z-Fold	Z-Fold	2-Sided Trim	Basic Punch	Staple		

Xerox® PrimeLink® C9065 and C9070 Printer

DEVICE SPECIFICATIONS	PRIMELINK C9065		PRIMELINK C9070				
IMPLEX SPEEDS	Color B	ack-and-white	Color	Black-and-white			
.5 x 11 in. / A4	Up to 65 ppm	Jp to 70 ppm	Up to 70 ppm	Up to 75 ppm			
1 x 17 in. / A3		Jp to 35 ppm	Up to 35 ppm	Up to 37 ppm			
2 x 18 in. / SRA3		Jp to 30 ppm	Up to 30 ppm	Up to 33 ppm			
UTO DUPLEX SPEEDS		ack-and-white	Color	Black-and-white			
.5 x 11 in. / A4		Jp to 70 ppm 2-sided	Up to 70 ppm 2-sided	Up to 75 ppm 2-sided			
		5 sheets per minute	35 sheets per minute	37 sheets per minute			
1 x 17 in. / A3		Jp to 35 ppm 2-sided	Up to 35 ppm 2-sided	Up to 37 ppm 2-sided			
		6 sheets per minute	17 sheets per minute	18 sheets per minute			
rinter Dimensions	Height: 54.8 in. / 1,391.5 mm; Width: 62 in./	1,574 mm; Depth: 31 in. / 787 mm					
Ionthly Duty Cycle	Up to 300,000 pages (maximum volume cap	acity expected in any one month, not ex	pected to be sustained on a regular basis)				
verage Monthly Print Volume (AMPV)	10,000 to 50,000 pages per month						
aper Flexibility/Weights	Standard Paper Capacity: 3,260 sheets (Tro	nv 1 & 2: 500 sheets Tray 3: 870 sheets 7	Tray 4: 1 140 sheets Tray 5 (Bynass): 250 she	ets)			
aper residency, recigined	Max Paper Capacity: 7,260 sheets (Tray 1 8 Sizes: Tray 1: 5.5 x 8.5 in. to 12 x 18 in. / A5 to Tray 4: 7.25 x 10.5 in., 8.5 x 11 in. / B5, A4; Ma	2: 500 sheets, Tray 3: 870 sheets, Tray 4: SRA3; Tray 2: 5.5 x 8.5 in. to 11 x 17 in. / /	: 1,140 sheets, Oversized High Capacity Tray	1 & 2: 4,000 sheets)			
mage Quality Print Technology	Benchmark image quality with 2400 x 2400 dpi resolution with VCSEL ROS and EA Eco with ultra-low melt technology toner for a smooth, offset-like finish						
Line Screens							
	150/200/300/600 dot screen, 200 line screen, stochastic and enhanced text and graphics • Advanced registration technology for tighter control						
Registration		~	uniformity (available on all configuration	5)			
rint Features	Print, copy, fax and scan, including		XLS sheet size (Tray 5 and OHCF) su	pporting up to 220gsm			
	Scan to PC, USB or Email, and mobile pr	inting	Up to 350 gsm (Tray 5 and OHCF or				
	Expansive media range lets you print even	•	auto-duplex up to 256 gsm (Bypass Tray and OHCF)				
		, ,					
	postcards to posters, both coated and uncoated stock, up to 350 gsm		 Xerox® replaceable units for toners, drums, fuser, charge corotron, waste bottle, staples 				
	Xerox Extensible Interface Platform® (EIP) allows you to						
	connect to third-party software solutions		Custom Paper Setup and Paper Catalog				
	Inline finishing options offer a professional polish with		Load-while-run toner and paper capability				
	banner printing, stapling, hole-punching, folding and booklet		Optional Features: Common Access Card Enablement				
	making for presentations, brochures, reports and newsletters						
	Kit, Accounting Options, Foreign Device Interface • Be secure with integrated security features such as						
	IP filtering, image overwrite, secure print, encrypted						
	Scan to Email, authentication and IPv6 support						
		··	0 .: 1				
ervers	Standard • Xerox® Integrated Color Server		Optional Xerox® EX-c C9065/C9070 Print Server Powered by Fiery® Xerox® EX-i C9065/C9070 Print Server Powered by Fiery® Xerox® EX C9065/C9070 Print Server Powered by Fiery®				
Integrated Scanner	Single-pass Duplex Automatic Docume	nt Feeder	 Up to 270 ipm (color, up to 200 gsm 				
	Color or black-and-white scanner		Up to 270 ipm (black-and-white, up	-			
	Scan to text searchable PDF, PDF/A, thu	mbnail preview, XPS®, PCL® 6, HP-GL2	Originals up to 11 x 17 in. (A3) in we				
	(direct submission), TIFF, JPEG		(16 lb. bond) to 200 gsm (53 lb. bon	d)			
	250-sheet capacity						
Optional Feeding	High Capacity Feeder (HCF): 2,000 sheets; 7.25 x 10.5 in., 8.5 x 11 in. / 184.2 x 266.7 mm, 279.4 x 215.9 mm (B5, A4);						
	16 lb. bond to 60 lb. cover / 64 to 220 gsm (uncoated and coated)						
	Optional Oversized High Capacity Feeder (OHCF):						
	One-Tray OHCF: 2,000 sheets plus Storage Cabinet; OHCF: 7.2 x 10 in./182 x 250 mm (B5) (up to 350 gsm) to 13 x 26 in./330 x 660 mm (up to 220 gsm).						
	Two-Tray OHCF: 4,000 sheets; 4 x 6 in. / 102 x	. 152 mm (up to 350 gsm) to 13 x 26 in./3					
	Two-Tray OHCF: 4,000 sheets; 4 x 6 in. / 102 x 152 mm (up to 350 gsm) to 13 x 26 in./330 x 660 mm (up to 220 gsm). Business Ready Finisher: Offsetting Top Tray: 500-sheets 8.5 x 11 in. / A4 unstapled. Stacking Stapling Tray: 3,000 sheets unstapled or 100 sets (dual or 4-position staple) 11x17 in., 8.5 x 14 in., A3 or 200 sets (single-position staple) 8.5 x 11 in. / A4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, Stapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to /						
Optional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p	osition staple) 8.5 x 11 in. / A4. Sizes: Sta	d. Stacking Stapling Tray: 3,000 sheets un: cking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, S	stapled or 100 sets (dual or 4-position stapl tapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to A			
Optional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu	osition staple) 8.5 x 11 in. / A4. Sizes: Sta nch and offset. Paper weights: Top Tray	d. Stacking Stapling Tray: 3,000 sheets un: cking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, S	stapled or 100 sets (dual or 4-position stap tapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to /			
Optional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu bond to 110 lb. cover / 60 to 256 gsm (coated	osition staple) 8.5 x 11 in. / A4. Sizes: Sta nch and offset. Paper weights: Top Tray l and uncoated).	d. Stacking Stapling Tray: 3,000 sheets un: cking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, S -16 lb. bond to 110 lb. cover / 60 to 350 gsm	stapled or 100 sets (dual or 4-position stap tapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to / (coated and uncoated). Stacker Tray-16 lb.			
ptional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu bond to 110 lb. cover / 60 to 256 gsm (coatec Business Ready Finisher Booklet Maker Fir	osition staple) 8.5 x 11 in. / A4. Sizes: Sta nch and offset. Paper weights: Top Tray l and uncoated). nisher: Offsetting Top Tray: 500-sheets	d. Stacking Stapling Tray: 3,000 sheets uncking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, S-16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in. / A4 unstapled. Stacking Stapling	stapled or 100 sets (dual or 4-position stap tapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to / (coated and uncoated). Stacker Tray-16 lb.			
ptional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu bond to 110 lb. cover / 60 to 256 gsm (coatec Business Ready Finisher Booklet Maker Fir (single position stapling or dual or 4-position s	osition staple) 8.5 x 11 in. / A4. Sizes: Sta nch and offset. Paper weights: Top Tray l and uncoated). nisher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A	d. Stacking Stapling Tray: 3,000 sheets un- cking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, S -16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or	stapled or 100 sets (dual or 4-position stap tapling: 7.25 x 10.5 in. to 11 x 17 in. / B5 to / coated and uncoated). Stacker Tray-16 lb. I Tray: 1,500 sheets unstapled or 200 sets			
ptional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu bond to 110 lb. cover / 60 to 256 gsm (coatec Business Ready Finisher Booklet Maker Fir (single position stapling or dual or 4-position s 200 sets (single-position staple) 8.5 x 11 in. / A	osition staple) 8.5 x 11 in. / A4. Sizes: Stanch and offset. Paper weights: Top Tray I and uncoated). sisher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A 4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. /	d. Stacking Stapling Tray: 3,000 sheets un- cking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, S -16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 1	stapled or 100 sets (dual or 4-position stap tapling: 7.25 x 10.5 in. to 11 x 17 in. / B5 to / coated and uncoated). Stacker Tray-16 lb. I Tray: 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3.			
ptional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu bond to 110 lb. cover / 60 to 256 gsm (coatec Business Ready Finisher Booklet Maker Fir (single position stapling or dual or 4-position s 200 sets (single-position staple) 8.5 x 11 in. / A Other; 5.5 x 8.5 in. / A5 output to top tray; pun	osition staple) 8.5 x 11 in. / A4. Sizes: Sta nch and offset. Paper weights: Top Tray land uncoated). nisher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A 4. Sizes: Stacking: 4 x 6 in. to 12 x 19.2 in., ch and offset. Paper weights: Top Tray-16	d. Stacking Stapling Tray: 3,000 sheets un- cking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, S -16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 1 6 lb. bond to 110 lb. cover / 60 to 350 gsm (cou	stapled or 100 sets (dual or 4-position stap tapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to / coated and uncoated). Stacker Tray-16 lb. I Tray: 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. ated and uncoated),			
ptional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu bond to 110 lb. cover / 60 to 256 gsm (coatec Business Ready Finisher Booklet Maker Fi (single position stapling or dual or 4-position s 200 sets (single-position staple) 8.5 x 11 in. / A Other; 5.5 x 8.5 in. / A5 output to top tray; pun Stacker Tray-16 lb. bond to 110 lb. cover / 60 to	osition staple) 8.5 x 11 in. / A4. Sizes: Stanch and offset. Paper weights: Top Trayland uncoated). nisher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A 4. Sizes: Stacking: 4 x 6 in. to 12 x 19.2 in., ch and offset. Paper weights: Top Tray-16: 256 gsm (coated and uncoated). Booklet	d. Stacking Stapling Tray: 3,000 sheets uncking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, S -16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 15 lb. bond to 110 lb. cover / 60 to 350 gsm (cor	stapled or 100 sets (dual or 4-position stap tapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to a coated and uncoated). Stacker Tray-16 lb. 1 Tray: 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. ted and uncoated), gsm			
ptional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu bond to 110 lb. cover / 60 to 256 gsm (coatee Business Ready Finisher Booklet Maker Fi (single position stapling or dual or 4-position s 200 sets (single-position staple) 8.5 x 11 in. / A Other; 5.5 x 8.5 in. / A5 output to top tray; pun Stacker Tray-16 lb. bond to 110 lb. cover / 60 to (coated and uncoated). Booklet Maker-Saddle	osition staple) 8.5 x 11 in. / A4. Sizes: Stanch and offset. Paper weights: Top Tray and uncoated). nisher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A 4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in., ch and offset. Paper weights: Top Tray-14.256 gsm (coated and uncoated). Booklet-stitch 2 to 16 sheets (7 sheets at 106 to 1	d. Stacking Stapling Tray: 3,000 sheets uncking; 4 x 6 in, to 12 x 19.2 in, / A6 to SRA3, S -16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in, / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in, to 11 x 1 6 lb. bond to 110 lb. cover / 60 to 350 gsm (co. Maker-16 lb. bond to 110 lb. cover / 60 to 256 76 gsm coated or 5 sheets at 177 to 220 gsm	stapled or 100 sets (dual or 4-position stap tapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to / coated and uncoated). Stacker Tray-16 lb. I Tray: 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. ated and uncoated), gsm coated).			
ptional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu bond to 110 lb. cover / 60 to 256 gsm (coatec Business Ready Finisher Booklet Maker Fii (single position stapling or dual or 4-position s 200 sets (single-position staple) 8.5 x 11 in. / A Other; 5.5 x 8.5 in. / A5 output to top tray; pun Stacker Tray-16 lb. bond to 110 lb. cover / 60 to (coated and uncoated). Booklet Maker-Saddle Production Ready Finisher (requires Interf	osition staple) 8.5 x 11 in. / A4. Sizes: Stanch and offset. Paper weights: Top Tray land uncoated), hisher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A 4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in., ch and offset. Paper weights: Top Tray-11 (256 gsm (coated and uncoated), Booklet stitch 2 to 16 sheets (7 sheets at 106 to 1 ace Decurler Module): Booklet Size: 100	d. Stacking Stapling Tray: 3,000 sheets uncking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, S -16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 1 5 lb. bond to 110 lb. cover / 60 to 350 gsm / Maker-16 lb. bond to 110 lb. cover / 60 to 256 / F6 gsm coated or 5 sheets at 177 to 220 gsm / Sheets (90 gsm) uncoated, 35 sheets (90 gsm)	stapled or 100 sets (dual or 4-position stap tapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to. (coated and uncoated). Stacker Tray-16 lb. If Tray: 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. ated and uncoated), gsm coated). sm) coated. Paper Size: 7.2 x 5.7*/182 x			
ptional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu bond to 110 lb. cover / 60 to 256 gsm (coatec Business Ready Finisher Booklet Maker Fii (single position stapling or dual or 4-position s 200 sets (single-position staple) 8.5 x 11 in. / A Other; 5.5 x 8.5 in. / A5 output to top tray; pun Stacker Tray-16 lb. bond to 110 b. cover / 60 to (coated and uncoated). Booklet Maker-Saddle Production Ready Finisher (requires Interl 146mm to 11.7 x 17"/297 x 432mm. Max Wei	osition staple) 8.5 x 11 in. / A4. Sizes: Stanch and offset. Paper weights: Top Tray I and uncoated). sisher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A 4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / ch and offset. Paper weights: Top Tray-16. 256 gsm (coated and uncoated). Booklet stitch 2 to 16 sheets (7 sheets at 106 to 1 ace Decurler Module): Booklet Size: 100 ght: 350 gsm. Options: Punch, Inserter ar	d. Stacking Stapling Tray: 3,000 sheets uncking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, S -16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 1 5 lb. bond to 110 lb. cover / 60 to 350 gsm / Maker-16 lb. bond to 110 lb. cover / 60 to 256 / F6 gsm coated or 5 sheets at 177 to 220 gsm / Sheets (90 gsm) uncoated, 35 sheets (90 gsm)	stapled or 100 sets (dual or 4-position stap tapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to. (coated and uncoated). Stacker Tray-16 lb. In Tray: 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. ated and uncoated), asm coated). sm) coated. Paper Size: 7.2 x 5.7*/182 x			
ptional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu bond to 110 lb. cover / 60 to 256 gsm (coatec Business Ready Finisher Booklet Maker Fir (single position stapling or dual or 4-position s 200 sets (single-position staple) 8.5 x 11 in. / A Other; 5.5 x 8.5 in. / A5 output to top tray; pun Stacker Tray-16 lb. bond to 110 lb. cover / 60 tc (coated and uncoated). Booklet Maker-Saddle Production Ready Finisher (requires Interf 146mm to 11.7 x 17"/29" x 432mm. Max Wei 5.75"/148 x 146mm to 13 x 19.2"/330 x 488m	osition staple) 8.5 x 11 in. / A4. Sizes: Stanch and offset. Paper weights: Top Trayland uncoated). isiher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A4. Sizes: Stacking: 4 x 6 in. to 12 x 19.2 in. / ch and offset. Paper weights: Top Tray-16: 256 gsm (coated and uncoated). Booklet settlich 2 to 16 sheets (7 sheets at 106 to 1 ace Decurler Module): Booklet Size: 100 ght: 350 gsm. Options: Punch, Inserter ar m.	d. Stacking Stapling Tray: 3,000 sheets uncking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, S-16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 1 6 lb. bond to 110 lb. cover / 60 to 350 gsm (cordinated for the stapling) Maker-16 lb. bond to 110 lb. cover / 60 to 256 Of 6 gsm coated or 5 sheets at 177 to 220 gsm O sheets (90 gsm) uncoated, 35 sheets (90 gsm) d C/Z Folder. Trays: Two output trays, 500-s	stapled or 100 sets (dual or 4-position stap tapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to / coated and uncoated). Stacker Tray-16 lb. 1 Tray: 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. sted and uncoated), gsm coated). sm) coated. Paper Size: 7.2 x 5.7*/182 x heet top tray, 3,000-sheet stack tray of 5.8			
ptional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu bond to 110 lb. cover / 60 to 256 gsm (coatee Business Ready Finisher Booklet Maker Fit (single position stapling or dual or 4-position s 200 sets (single-position staple) 8.5 x 11 in. / A Other; 5.5 x 8.5 in. / A5 output to top tray; pun Stacker Tray-16 lb. bond to 110 lb. cover / 60 tk (coated and uncoated). Booklet Maker-Saddle Production Ready Finisher (requires Interf 146mm to 11.7 x 17"/297 x 432mm. Max Wei 5.75"/148 x 146mm to 13 x 19.2"/330 x 488m Production Ready Finisher Plus (requires I	osition staple) 8.5 x 11 in. / A4. Sizes: Stanch and offset. Paper weights: Top Trayland uncoated). inisher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A 4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / ch and offset. Paper weights: Top Tray-16: 256 gsm (coated and uncoated). Booklet-stitch 2 to 16 sheets (7 sheets at 106 to 1 ace Decurler Module): Booklet Size: 100 gght: 350 gsm. Options: Punch, Inserter ar m. interface Decurler Module): Provides sa	d. Stacking Stapling Tray: 3,000 sheets uncking; 4 x 6 in, to 12 x 19.2 in, / A6 to SRA3, S -16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in, / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 1 6 lb. bond to 110 lb. cover / 60 to 350 gsm (cor Maker-16 lb. bond to 110 lb. cover / 60 to 256 76 gsm coated or 5 sheets at 177 to 220 gsm a sheets (90 gsm) uncoated, 35 sheets (90 gsm) and C/Z Folder. Trays: Two output trays, 500-s me function as the Production Ready Finish.	stapled or 100 sets (dual or 4-position stap tapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to. coated and uncoated). Stacker Tray-16 lb. 1 Tray: 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. sted and uncoated), gsm coated). sm) coated. Paper Size: 7.2 x 5.7*/182 x heet top tray, 3,000-sheet stack tray of 5.8			
ptional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu bond to 110 lb. cover / 60 to 256 gsm (coatec Business Ready Finisher Booklet Maker Fit (single position stapling or dual or 4-positions 200 sets (single-position staple) 8.5 x 11 in. / A Other; 5.5 x 8.5 in. / A5 output to top tray; pun Stacker Tray-16 lb. bond to 110 lb. cover / 60 to (coated and uncoated). Booklet Maker-Saddle Production Ready Finisher (requires Interf 146mm to 11.7 x 177/297 x 432mm. Max Wei 5.75*/148 x 146mm to 13 x 19.2*/330 x 488m Production Ready Finisher Plus (requires I stacker tray. Used to connect third-party inlir	osition staple) 8.5 x 11 in. / A4. Sizes: Stanch and offset. Paper weights: Top Tray land uncoated), nisher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A 4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / ch and offset. Paper weights: Top Tray-11 (-256 gsm (coated and uncoated), Booklet -stitch 2 to 16 sheets (7 sheets at 106 to 1 ace Decurler Module): Booklet Size: 100 ght: 350 gsm. Options: Punch, Inserter ar months of the state of the	d. Stacking Stapling Tray: 3,000 sheets uncking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, S-16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 1 6 lb. bond to 110 lb. cover / 60 to 350 gsm (co . Maker-16 lb. bond to 110 lb. cover / 60 to 256 76 gsm coated or 5 sheets at 177 to 220 gsm 0 sheets (90 gsm) uncoated, 35 sheets (90 gsm) dC/Z Folder. Trays: Two output trays, 500-seme function as the Production Ready Finisher Finishing Interface Module.	stapled or 100 sets (dual or 4-position stap tapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to. (coated and uncoated). Stacker Tray-16 lb. In Tray: 1,500 sheets unstapled or 200 sets in. / B5 to A3. steed and uncoated), gsm coated). sim) coated. Paper Size: 7.2 x 5.7*/182 x heet top tray, 3,000-sheet stack tray of 5.8 er with a 500-sheet top tray and 2,000-sheet stop tray and 2,000-sheet stack tray of sheet with a 500-sheet top tray and 2,000-sheet stack tray of sheet with a 500-sheet top tray and 2,000-sheet stack tray of sheet with a 500-sheet top tray and 2,000-sheet stack tray of sheet with a 500-sheet top tray and 2,000-sheet stack tray of sheet stack tray of sheet stack tray of sheet top tray and 2,000-sheet stack tray of sheet sh			
ptional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu bond to 110 lb. cover / 60 to 256 gsm (coatec Business Ready Finisher Booklet Maker Fii (single position stapling or dual or 4-position s 200 sets (single-position staple) 8.5 x 11 in. / A Other; 5.5 x 8.5 in. / A5 output to top tray; pun Stacker Tray-16 lb. bond to 110 lb. cover / 60 tc (coated and uncoated). Booklet Maker-Saddle Production Ready Finisher (requires Interl 146mm to 11.7 x 17"/297 x 432mm. Max Wei 5.75"/148 x 146mm to 13 x 19.2"/330 x 488m Production Ready Finisher Plus (requires I stacker tray. Used to connect third-party inlir Production Ready Finisher with Booklet M	osition staple) 8.5 x 11 in. / A4. Sizes: Stanch and offset. Paper weights: Top Tray land uncoated). nisher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A 4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in., ch and offset. Paper weights: Top Tray-16. 256 gsm (coated and uncoated). Booklet -stitch 2 to 16 sheets (7 sheets at 106 to 16 ace Decurler Module): Booklet Size: 106 ght: 350 gsm. Options: Punch, Inserter arm. nterface Decurler Module): Provides sa le finishing options. Includes PFIM Partne aker (requires Interface Decurler Module) excurler Module.	d. Stacking Stapling Tray: 3,000 sheets uncking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, S-16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 1 5 lb. bond to 110 lb. cover / 60 to 350 gsm (Maker-16 lb. bond to 110 lb. cover / 60 to 256 76 gsm coated or 5 sheets at 177 to 220 gsm of Sheets (90 gsm) uncoated, 35 sheets (90 gsm) d C/Z Folder. Trays: Two output trays, 500-seme function as the Production Ready Finisher Finishing Interface Module. ule): Booklet Size: 7.17 x 10.1*/182 x 257mm	stapled or 100 sets (dual or 4-position stap tapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to. (coated and uncoated). Stacker Tray-16 lb. In Tray: 1,500 sheets unstapled or 200 sets of in. / B5 to A3. Steed and uncoated), gsm coated. Stacker Tray-16 lb. (sm) coated. Paper Size: 7.2 x 5.7*/182 x heet top tray, 3,000-sheet stack tray of 5.8 ser with a 500-sheet top tray and 2,000-sheet to 13 x 19.2*/330 x 488mm up to 350 gsm.			
ptional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu bond to 110 lb. cover / 60 to 256 gsm (coate Business Ready Finisher Booklet Maker Fii (single position stapling or dual or 4-position s 200 sets (single-position staple) 8.5 x 11 in. / A Other; 5.5 x 8.5 in. / A5 output to top tray; pun Stacker Tray-16 lb. bond to 110 lb. cover / 60 to (coated and uncoated). Booklet Maker-Saddle Production Ready Finisher (requires Interl 146mm to 11.7 x 17"/297 x 432mm. Max Wei 5.75"/148 x 146mm to 13 x 19.2"/330 x 488m Production Ready Finisher Plus (requires I stacker tray. Used to connect third-party inlir Production Ready Finisher with Booklet M Trays: 500-sheet top tray, 2,000-sheet stacks	osition staple) 8.5 x 11 in. / A4. Sizes: Stanch and offset. Paper weights: Top Tray land uncoated). nisher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A 4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in., ch and offset. Paper weights: Top Tray-16. 256 gsm (coated and uncoated). Booklet -stitch 2 to 16 sheets (7 sheets at 106 to 16 ace Decurler Module): Booklet Size: 106 ght: 350 gsm. Options: Punch, Inserter arm. nterface Decurler Module): Provides sa le finishing options. Includes PFIM Partne aker (requires Interface Decurler Module) excurler Module.	d. Stacking Stapling Tray: 3,000 sheets uncking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, S -16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 1 5 lb. bond to 110 lb. cover / 60 to 350 gsm (Maker-16 lb. bond to 110 lb. cover / 60 to 256 76 gsm coated or 5 sheets at 177 to 220 gsm of sheets (90 gsm) uncoated, 35 sheets (90 gsm) d C/Z Folder. Trays: Two output trays, 500-seme function as the Production Ready Finisher Finishing Interface Module. ule): Booklet Size: 7.17 x 10.1*/182 x 257mm	stapled or 100 sets (dual or 4-position stap tapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to (coated and uncoated). Stacker Tray-16 lb. In Tray: 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. atted and uncoated), asm coated). Sim) coated. Paper Size: 7.2 x 5.7°/182 x sheet top tray, 3,000-sheet stack tray of 5.8 er with a 500-sheet top tray and 2,000-sheet to 13 x 19.2°/330 x 488mm up to 350 gsm			
ptional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu bond to 110 lb. cover / 60 to 256 gsm (coatec Business Ready Finisher Booklet Maker Fir (single position stapling or dual or 4-position s 200 sets (single-position staple) 8.5 x 11 in. / A Other; 5.5 x 8.5 in. / A5 output to top tray; pun Stacker Tray-16 lb. bond to 110 lb. cover / 60 tc (coated and uncoated). Booklet Maker-Saddle Production Ready Finisher (requires Interl 146mm to 11.7 x 17"/297 x 432mm. Max Wei 5.75"/148 x 146mm to 13 x 19.2"/330 x 488m Production Ready Finisher Plus (requires I stacker tray. Used to connect third-party interproduction Ready Finisher with Booklet M Trays: 500-sheet top tray, 2,000-sheet stacker Catch Tray: 500-sheet stacking.	osition staple) 8.5 x 11 in. / A4. Sizes: Stanch and offset. Paper weights: Top Trayland uncoated). isiher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A 4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in., ch and offset. Paper weights: Top Tray-16. 256 gsm (coated and uncoated). Booklet -stitch 2 to 16 sheets (7 sheets at 106 to 1 acc Decurler Module): Booklet Size: 100 ght: 350 gsm. Options: Punch, Inserter ar m. nterface Decurler Module): Provides sa ee finisching options. Includes PrIM Partne aker (requires Interface Decurler Module): acker (requires Interface Decurler Module): 120 gray, saddle-stitch booklet tray (up to 120 gray, saddle-stitch booklet tray (up to 120 gray).	d. Stacking Stapling Tray: 3,000 sheets uncking; 4 x 6 in, to 12 x 19.2 in. / A6 to SRA3, S-16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 1 6 lb. bond to 110 lb. cover / 60 to 350 gsm (cor Maker-16 lb. bond to 110 lb. cover / 60 to 256 76 gsm coated or 5 sheets at 177 to 220 gsm 0 sheets (90 gsm) uncoated, 35 sheets (90 gsm) od C/Z Folder. Trays: Two output trays, 500-s me function as the Production Ready Finisher Finishing Interface Module. ule): Booklet Size: 7.17 x 10.1*/182 x 257mm of pages, 30 sheets/90 gsm uncoated, 25 she	stapled or 100 sets (dual or 4-position staptapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to. (coated and uncoated). Stacker Tray-16 lb. 1 Tray: 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. ated and uncoated), gsm coated). m) coated. Paper Size: 7.2 x 5.7*/182 x heet top tray, 3,000-sheet stack tray of 5.8 er with a 500-sheet top tray and 2,000-sheet to 13 x 19.2*/330 x 488mm up to 350 gsm. ets/90 gsm coated).			
ptional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu bond to 110 lb. cover / 60 to 256 gsm (coatec Business Ready Finisher Booklet Maker Fit (single position stapling or dual or 4-positions 200 sets (single-position staple) 8.5 x 11 in. / A Other; 5.5 x 8.5 in. / A5 output to top tray; pu Stacker Tray-16 lb. bond to 110 lb. cover / 60 to (coated and uncoated). Booklet Maker-Saddle Production Ready Finisher (requires Interf 146mm to 11.7 x 17*297 x 432mm. Max Wei 5.75*/148 x 146mm to 13 x 19.2*/330 x 488m Production Ready Finisher Plus (requires I stacker tray. Used to connect third-party inlir Production Ready Finisher with Booklet M Trays: 500-sheet tacking. Xerox® SquareFold® Trimmer Module: Face	osition staple) 8.5 x 11 in. / A4. Sizes: Stanch and offset. Paper weights: Top Tray land uncoated). nisher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A 4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in., ch and offset. Paper weights: Top Tray-16.256 gsm (coated and uncoated). Booklet-stitch 2 to 16 sheets (7 sheets at 106 to 1 acc Decurler Module): Booklet Size: 100 ght: 350 gsm. Options: Punch, Inserter arm. nterface Decurler Module): Provides sale finishing options. Includes PFIM Partne aker (requires Interface Decurler Moduray, saddle-stitch booklet tray (up to 120 erry, saddle-stitch booklet tray (up to 120 errim: 120 pages (30 sheets). Compatibil	d. Stacking Stapling Tray: 3,000 sheets uncking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, S -16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 1 5 lb. bond to 110 lb. cover / 60 to 350 gsm (co. Maker-16 lb. bond to 110 lb. cover / 60 to 256 76 gsm coated or 5 sheets at 177 to 220 gsm 0 sheets (90 gsm) uncoated, 35 sheets (90 gsm) dc //Z Folder. Trays: Two output trays, 500-s me function as the Production Ready Finisher Finishing Interface Module. ule): Booklet Size: 7.17 x 10.17/182 x 257mm 0 pages, 30 sheets/90 gsm uncoated, 25 she lity: Production Ready Finisher, Booklet Make	stapled or 100 sets (dual or 4-position stap tapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to. (coated and uncoated). Stacker Tray-16 lb. 1 Tray: 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. atted and uncoated), gsm coated). sm) coated. Paper Size: 7.2 x 5.7*/182 x heet top tray, 3,000-sheet stack tray of 5.8 er with a 500-sheet top tray and 2,000-she to 13 x 19.2*/330 x 488mm up to 350 gsm. ets/90 gsm coated). er, Crease and Two-Sided Trimmer.			
ptional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu bond to 110 lb. cover / 60 to 256 gsm (coatec Business Ready Finisher Booklet Maker Fii (single position stapling or dual or 4-position s 200 sets (single-position staple) 8.5 x 11 in. / A Other; 5.5 x 8.5 in. / A5 output to top tray; pun Stacker Tray-16 lb. bond to 110 lb. cover / 60 tc (coated and uncoated). Booklet Maker-Saddle Production Ready Finisher (requires Interf 146mm to 11.7 x 177/297 x 432mm. Max Wei 5.75*/148 x 146mm to 13 x 19.2*/330 x 488m Production Ready Finisher Plus (requires I stacker tray. Used to connect third-party inlin Production Ready Finisher with Booklet M Trays: 500-sheet top tray, 2,000-sheet stackin Offset Catch Tray: 500-sheet stacking. Xerox* SquareFold* Trimmer Module: Facc Xerox* C/Z Folder: Sheet Size: 8.5 x 11* (A4).	osition staple) 8.5 x 11 in. / A4. Sizes: Stanch and offset. Paper weights: Top Tray land uncoated). nisher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A 4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in., ch and offset. Paper weights: Top Tray-16.256 gsm (coated and uncoated). Booklet-stitch 2 to 16 sheets (7 sheets at 106 to 1 acc Decurler Module): Booklet Size: 100 ght: 350 gsm. Options: Punch, Inserter arm. nterface Decurler Module): Provides sale finishing options. Includes PFIM Partne aker (requires Interface Decurler Moduray, saddle-stitch booklet tray (up to 120 erry, saddle-stitch booklet tray (up to 120 errim: 120 pages (30 sheets). Compatibil	d. Stacking Stapling Tray: 3,000 sheets uncking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, S -16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 1 5 lb. bond to 110 lb. cover / 60 to 350 gsm (co. Maker-16 lb. bond to 110 lb. cover / 60 to 256 76 gsm coated or 5 sheets at 177 to 220 gsm 0 sheets (90 gsm) uncoated, 35 sheets (90 gsm) dc //Z Folder. Trays: Two output trays, 500-s me function as the Production Ready Finisher Finishing Interface Module. ule): Booklet Size: 7.17 x 10.17/182 x 257mm 0 pages, 30 sheets/90 gsm uncoated, 25 she lity: Production Ready Finisher, Booklet Make	stapled or 100 sets (dual or 4-position stap tapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to. (coated and uncoated). Stacker Tray-16 lb. 1 Tray: 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. atted and uncoated), gsm coated). sm) coated. Paper Size: 7.2 x 5.7*/182 x heet top tray, 3,000-sheet stack tray of 5.8 er with a 500-sheet top tray and 2,000-she to 13 x 19.2*/330 x 488mm up to 350 gsm. ets/90 gsm coated). er, Crease and Two-Sided Trimmer.			
Optional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu bond to 110 lb. cover / 60 to 256 gsm (coatec Business Ready Finisher Booklet Maker Fii (single position stapling or dual or 4-position s 200 sets (single-position staple) 8.5 x 11 in. / A Other; 5.5 x 8.5 in. / A5 output to top tray; pun Stacker Tray-16 lb. bond to 110 lb. cover / 60 to (coated and uncoated). Booklet Maker-Saddle Production Ready Finisher (requires Interl 146mm to 11.7 x 17"/297 x 432mm. Max Wei 5.75"/148 x 146mm to 13 x 19.2"/330 x 488m Production Ready Finisher Plus (requires I stacker tray. Used to connect third-party inlir Production Ready Finisher with Booklet M Trays: 500-sheet top tray, 2,000-sheet stacking. Xerox® SquareFold® Trimmer Module: Facc Xerox® C/Z Folder: Sheet Size: 8.5 x 11" (A4) Finisher, Booklet Maker.	osition staple) 8.5 x 11 in. / A4. Sizes: Stanch and offset. Paper weights: Top Trayland uncoated). Inisher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A 4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in., ch and offset. Paper weights: Top Tray-16. 256 gsm (coated and uncoated). Booklet -stitch 2 to 16 sheets (7 sheets at 106 to 16 ace Decurler Module): Booklet Size: 106 ght: 350 gsm. Options: Punch, Inserter arm. Interface Decurler Module): Provides sale finishing options. Includes PFIM Partne aker (requires Interface Decurler Moduray, saddle-stitch booklet tray (up to 120 per Trim: 120 pages (30 sheets). Compatibil Half-Z Fold Sheet Size: Larger stocks redi	d. Stacking Stapling Tray: 3,000 sheets uncking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, S-16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 1 5 lb. bond to 110 lb. cover / 60 to 350 gsm (co. Maker-16 lb. bond to 110 lb. cover / 60 to 256 76 gsm coated or 5 sheets at 177 to 220 gsm 0 sheets (90 gsm) uncoated, 35 sheets (90 gsm) dc //Z Folder. Trays: Two output trays, 500-s me function as the Production Ready Finisher Finishing Interface Module. ule): Booklet Size: 7.17 x 10.1*/182 x 257mm or pages, 30 sheets/90 gsm uncoated, 25 sheelity: Production Ready Finisher, Booklet Makucing to 8.5 x 11" (A4). Weight Range: 64 - 90	istapled or 100 sets (dual or 4-position stap tapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to. (coated and uncoated). Stacker Tray-16 lb. In Tray: 1,500 sheets unstapled or 200 sets of in. / B5 to A3. (steed and uncoated), gsm. coated). Signary coated. Signary coated and uncoated of 5.8 ser with a 500-sheet top tray and 2,000-sheet top tray. 3,000-sheet stack tray of 5.8 ser with a 500-sheet top tray and 2,000-sheet top 13 x 19.2°/330 x 488mm up to 350 gsm. ets/90 gsm. coated).			
Optional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu bond to 110 lb. cover / 60 to 256 gsm (coated Business Ready Finisher Booklet Maker Fit (single position stapling or dual or 4-position s 200 sets (single-position staple) 8.5 x 11 in. / A Other; 5.5 x 8.5 in. / A5 output to top tray; pun Stacker Tray-16 lb. bond to 110 b. cover / 60 to (coated and uncoated). Booklet Maker-Saddle Production Ready Finisher (requires Interl 146mm to 11.7 x 17"/297 x 432mm. Max Wei 5.75"/148 x 146mm to 13 x 19.2"/330 x 488m Production Ready Finisher Plus (requires I stacker tray. Used to connect third-party inlir Production Ready Finisher with Booklet M Trays: 500-sheet top tray, 2,000-sheet stacking. Xerox® SquareFold® Trimmer Module: Facc Xerox® C/Z Folder: Sheet Size: 8.5 x 11" (A4). Finisher, Booklet Maker.	osition staple) 8.5 x 11 in. / A4. Sizes: Stanch and offset. Paper weights: Top Tray I and uncoated). I and uncoated). Sisher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A 4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in., ch and offset. Paper weights: Top Tray-16. 256 gsm (coated and uncoated). Booklet stitch 2 to 16 sheets (7 sheets at 106 to 1 ace Decurler Module): Booklet Size: 100 ght: 350 gsm. Options: Punch, Inserter arm. Interface Decurler Module): Provides sale finishing options. Includes PFIM Partne aker (requires Interface Decurler Moduray, saddle-stitch booklet tray (up to 120 et arm.) Partim: 120 pages (30 sheets). Compatibil Half-Z Fold Sheet Size: Larger stocks redibilities: Trimming, punching, folding, sta	d. Stacking Stapling Tray: 3,000 sheets uncking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, S-16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 1 5 lb. bond to 110 lb. cover / 60 to 350 gsm (co. Maker-16 lb. bond to 110 lb. cover / 60 to 256 76 gsm coated or 5 sheets at 177 to 220 gsm 0 sheets (90 gsm) uncoated, 35 sheets (90 gsm) dc //Z Folder. Trays: Two output trays, 500-s me function as the Production Ready Finisher Finishing Interface Module. ule): Booklet Size: 7.17 x 10.1*/182 x 257mm or pages, 30 sheets/90 gsm uncoated, 25 sheelity: Production Ready Finisher, Booklet Makucing to 8.5 x 11" (A4). Weight Range: 64 - 90	istapled or 100 sets (dual or 4-position stap tapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to. (coated and uncoated). Stacker Tray-16 lb. In Tray: 1,500 sheets unstapled or 200 sets of in. / B5 to A3. (steed and uncoated), gsm. coated). Signary coated. Signary coated and uncoated of 5.8 ser with a 500-sheet top tray and 2,000-sheet top tray. 3,000-sheet stack tray of 5.8 ser with a 500-sheet top tray and 2,000-sheet top 13 x 19.2°/330 x 488mm up to 350 gsm. ets/90 gsm. coated).			
Optional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu bond to 110 lb. cover / 60 to 256 gsm (coatec Business Ready Finisher Booklet Maker Fit (single position stapling or dual or 4-positions 200 sets (single-position staple) 8.5 x 11 in. / A Other; 5.5 x 8.5 in. / A5 output to top tray; pu Stacker Tray-16 lb. bond to 110 lb. cover / 60 to (coated and uncoated). Booklet Maker-Saddle Production Ready Finisher (requires Interf 146mm to 11.7 **17'297 x 432mm. Max Wei 5.75'/148 x 146mm to 13 x 19.2"/330 x 488m Production Ready Finisher Plus (requires I stacker tray. Used to connect third-party inlir Production Ready Finisher with Booklet M Trays: 500-sheet stacking. Xerox® SquareFold® Trimmer Module: Fact Xerox® C/Z Folder: Sheet Size: 8.5 x 11" (A4) Finisher, Booklet Maker. Xerox® Inserter: Capacity: 250 sheets. Capa Weight: 350 gsm. Compatibility: Production	osition staple) 8.5 x 11 in. / A4. Sizes: Stanch and offset. Paper weights: Top Tray land uncoated). nisher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A 4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in., ch and offset. Paper weights: Top Tray-16.256 gsm (coated and uncoated). Booklet-stitch 2 to 16 sheets (7 sheets at 106 to 1 ace Decurler Module): Booklet Size: 100 ght: 350 gsm. Options: Punch, Inserter arm. nterface Decurler Module): Provides sale finishing options. Includes PFIM Partne aker (requires Interface Decurler Moduray, saddle-stitch booklet tray (up to 120 e Trim: 120 pages (30 sheets). Compatibil Half-Z Fold Sheet Size: Larger stocks redubilities: Trimming, punching, folding, staleady Finisher.	d. Stacking Stapling Tray: 3,000 sheets uncking; 4 x 6 in, to 12 x 19.2 in. / A6 to SRA3, S-16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 1 5 lb. bond to 110 lb. cover / 60 to 350 gsm (co. Maker-16 lb. bond to 110 lb. cover / 60 to 256 76 gsm coated or 5 sheets at 177 to 220 gsm 0 sheets (90 gsm) uncoated, 35 sheets (90 gsn) of CZ Folder. Trays: Two output trays, 500-s me function as the Production Ready Finisher Finishing Interface Module. ule): Booklet Size: 7.17 x 10.11/182 x 257mm 0 pages, 30 sheets/90 gsm uncoated, 25 she lity: Production Ready Finisher, Booklet Makucing to 8.5 x 11" (A4). Weight Range: 64 - 90 pling, stacking. Paper Size: 7.2 x 5.8" (182 x 1)	stapled or 100 sets (dual or 4-position stap tapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to. (coated and uncoated). Stacker Tray-16 lb. 1 Tray: 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. ated and uncoated), gsm coated), sm) coated. Paper Size: 7.2 x 5.7*/182 x heet top tray, 3,000-sheet stack tray of 5.8 er with a 500-sheet top tray and 2,000-she to 13 x 19.2*/330 x 488mm up to 350 gsm. ets/90 gsm coated). er, Crease and Two-Sided Trimmer. logsm. Compatibility: Production Ready 48 mm) to 13 x 19.2* (330 x 488 mm). Max			
Optional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-pother; 5.5 x 8.5 in. / A5 output to top tray; pubond to 110 lb. cover / 60 to 256 gsm (coatec Business Ready Finisher Booklet Maker Fin (single position stapling or dual or 4-positions 200 sets (single-position staple) 8.5 x 11 in. / A Other; 5.5 x 8.5 in. / A5 output to top tray; pun Stacker Tray-16 lb. bond to 110 lb. cover / 60 to (coated and uncoated). Booklet Maker-Saddle Production Ready Finisher (requires Interf 146mm to 11.7 x 177/297 x 432mm. Max Wei 5.75*/148 x 146mm to 13 x 19.2*/330 x 488m Production Ready Finisher Plus (requires I stacker tray. Used to connect third-party inlir Production Ready Finisher with Booklet M Trays: 500-sheet top tray, 2,000-sheet stack offset Catch Tray: 500-sheet stacking. Xerox® SquareFold® Trimmer Module: Facc Xerox® C/Z Folder: Sheet Size: 8.5 x 11* (A4). Finisher, Booklet Maker. Xerox® Inserter: Capacity: 250 sheets. Capa Weight: 350 gsm. Compatibility: Production Xerox® Crease/Two-sided Trimmer: Trim Ref	osition staple) 8.5 x 11 in. / A4. Sizes: Stanch and offset. Paper weights: Top Tray land uncoated). nisher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A 4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / ch and offset. Paper weights: Top Tray: 10.256 gsm (coated and uncoated). Booklet -stitch 2 to 16 sheets (7 sheets at 106 to 1 ace Decurler Module): Booklet Size: 100 ght: 350 gsm. Options: Punch, Inserter ar m. nterface Decurler Module): Provides sate finishing options. Includes PFIM Partne alker (requires Interface Decurler Moduray, saddle-stitch booklet tray (up to 120 et 7 irm: 120 pages (30 sheets). Compatibil Half-Z Fold Sheet Size: Larger stocks redustles: Trimming, punching, folding, stated prinisher. lange: 0.236" (6 mm) to 0.985" (25 mm). P	d. Stacking Stapling Tray: 3,000 sheets uncking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, S-16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 1 fbl. bond to 110 lb. cover / 60 to 350 gsm (co. Maker-16 lb. bond to 110 lb. cover / 60 to 256 76 gsm coated or 5 sheets at 177 to 220 gsm 0 sheets (90 gsm) uncoated, 35 sheets (90 gsm) dc/Z Folder. Trays: Two output trays, 500-s me function as the Production Ready Finisher Finishing Interface Module. ule): Booklet Size: 7.17 x 10.1"/182 x 257mm 0 pages, 30 sheets/90 gsm uncoated, 25 she lity: Production Ready Finisher, Booklet Mak ucing to 8.5 x 11" (A4). Weight Range: 64 - 90 pling, stacking. Paper Size: 7.2 x 5.8" (182 x 1 aper Size: 7.7 x 8.3"/194 x 210 mm to 13 x 19	citapled or 100 sets (dual or 4-position stap tapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to. (coated and uncoated). Stacker Tray-16 lb. 1 Tray: 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. atted and uncoated), gsm coated). sm) coated. Paper Size: 7.2 x 5.7"/182 x heet top tray, 3,000-sheet stack tray of 5.8 er with a 500-sheet top tray and 2,000-she to 13 x 19.2"/330 x 488mm up to 350 gsm. ets/90 gsm coated). er, Crease and Two-Sided Trimmer. 10 gsm. Compatibility: Production Ready 48 mm) to 13 x 19.2" (330 x 488 mm). Max 2"/330 x 488 mm.			
Optional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu bond to 110 lb. cover / 60 to 256 gsm (coatec Business Ready Finisher Booklet Maker Fit (single position stapling or dual or 4-positions 200 sets (single-position staple) 8.5 x 11 in. / A Other; 5.5 x 8.5 in. / A5 output to top tray; pu Stacker Tray-16 lb. bond to 110 lb. cover / 60 to (coated and uncoated). Booklet Maker-Saddle Production Ready Finisher (requires Interf 146mm to 11.7 **17'297 x 432mm. Max Wei 5.75'/148 x 146mm to 13 x 19.2"/330 x 488m Production Ready Finisher Plus (requires I stacker tray. Used to connect third-party inlir Production Ready Finisher with Booklet M Trays: 500-sheet stacking. Xerox® SquareFold® Trimmer Module: Fact Xerox® C/Z Folder: Sheet Size: 8.5 x 11" (A4) Finisher, Booklet Maker. Xerox® Inserter: Capacity: 250 sheets. Capa Weight: 350 gsm. Compatibility: Production	osition staple) 8.5 x 11 in. / A4. Sizes: Stanch and offset. Paper weights: Top Tray land uncoated). nisher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A 4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in. / ch and offset. Paper weights: Top Tray: 10.256 gsm (coated and uncoated). Booklet -stitch 2 to 16 sheets (7 sheets at 106 to 1 ace Decurler Module): Booklet Size: 100 ght: 350 gsm. Options: Punch, Inserter ar m. nterface Decurler Module): Provides sate finishing options. Includes PFIM Partne alker (requires Interface Decurler Moduray, saddle-stitch booklet tray (up to 120 et 7 irm: 120 pages (30 sheets). Compatibil Half-Z Fold Sheet Size: Larger stocks redustles: Trimming, punching, folding, stated prinisher. lange: 0.236" (6 mm) to 0.985" (25 mm). P	d. Stacking Stapling Tray: 3,000 sheets uncking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, S-16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 1 fbl. bond to 110 lb. cover / 60 to 350 gsm (co. Maker-16 lb. bond to 110 lb. cover / 60 to 256 76 gsm coated or 5 sheets at 177 to 220 gsm 0 sheets (90 gsm) uncoated, 35 sheets (90 gsm) dc/Z Folder. Trays: Two output trays, 500-s me function as the Production Ready Finisher Finishing Interface Module. ule): Booklet Size: 7.17 x 10.1"/182 x 257mm 0 pages, 30 sheets/90 gsm uncoated, 25 she lity: Production Ready Finisher, Booklet Mak ucing to 8.5 x 11" (A4). Weight Range: 64 - 90 pling, stacking. Paper Size: 7.2 x 5.8" (182 x 1 aper Size: 7.7 x 8.3"/194 x 210 mm to 13 x 19	citapled or 100 sets (dual or 4-position stap tapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to. (coated and uncoated). Stacker Tray-16 lb. 1 Tray: 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. atted and uncoated), gsm coated). sm) coated. Paper Size: 7.2 x 5.7"/182 x heet top tray, 3,000-sheet stack tray of 5.8 er with a 500-sheet top tray and 2,000-she to 13 x 19.2"/330 x 488mm up to 350 gsm. ets/90 gsm coated). er, Crease and Two-Sided Trimmer. 10 gsm. Compatibility: Production Ready 48 mm) to 13 x 19.2" (330 x 488 mm). Max 2"/330 x 488 mm.			
Optional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-pother; 5.5 x 8.5 in. / A5 output to top tray; pubond to 110 lb. cover / 60 to 256 gsm (coatec Business Ready Finisher Booklet Maker Fin (single position stapling or dual or 4-positions 200 sets (single-position staple) 8.5 x 11 in. / A Other; 5.5 x 8.5 in. / A5 output to top tray; pun Stacker Tray-16 lb. bond to 110 lb. cover / 60 to (coated and uncoated). Booklet Maker-Saddle Production Ready Finisher (requires Interf 146mm to 11.7 x 177/297 x 432mm. Max Wei 5.75*/148 x 146mm to 13 x 19.2*/330 x 488m Production Ready Finisher Plus (requires I stacker tray. Used to connect third-party inlir Production Ready Finisher with Booklet M Trays: 500-sheet top tray, 2,000-sheet stack offset Catch Tray: 500-sheet stacking. Xerox® SquareFold® Trimmer Module: Facc Xerox® C/Z Folder: Sheet Size: 8.5 x 11* (A4). Finisher, Booklet Maker. Xerox® Inserter: Capacity: 250 sheets. Capa Weight: 350 gsm. Compatibility: Production Xerox® Crease/Two-sided Trimmer: Trim Ref	osition staple) 8.5 x 11 in. / A4. Sizes: Stanch and offset. Paper weights: Top Tray land uncoated). nisher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A 4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in., ch and offset. Paper weights: Top Tray-16: 256 gsm (coated and uncoated). Booklet - stitch 2 to 16 sheets (7 sheets at 106 to 16 ace Decurler Module): Booklet Size: 100 ght: 350 gsm. Options: Punch, Inserter arm. nterface Decurler Module): Provides sa ite finishing options. Includes PFIM Partne aker (requires Interface Decurler Module): 27 modules: 120 gray, saddle-stitch booklet tray (up to 120 get Trim: 120 pages (30 sheets). Compatibil Half-Z Fold Sheet Size: Larger stocks redistillities: Trimming, punching, folding, sta Ready Finisher. lange: 0.236" (6 mm) to 0.985" (25 mm). Ption Ready Finisher and Booklet Maker. B	d. Stacking Stapling Tray: 3,000 sheets uncking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, S-16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 1 5 lb. bond to 110 lb. cover / 60 to 350 gsm (co . Maker-16 lb. bond to 110 lb. cover / 60 to 256 76 gsm coated or 5 sheets at 177 to 220 gsm 0 sheets (90 gsm) uncoated, 35 sheets (90 gsm) dc //Z Folder. Trays: Two output trays, 500-s me function as the Production Ready Finisher Finishing Interface Module. ule): Booklet Size: 7.17 x 10.1*/182 x 257mm pages, 30 sheets/90 gsm uncoated, 25 she lity: Production Ready Finisher, Booklet Mak ucing to 8.5 x 11" (A4). Weight Range: 64 - 90 pling, stacking. Paper Size: 7.2 x 5.8* (182 x 1 aper Size: 7.7 x 8.3*/194 x 210 mm to 13 x 19 suffering Unit: Up to five customizable mount	istapled or 100 sets (dual or 4-position staptapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to (coated and uncoated). Stacker Tray-16 lb. 1 Tray: 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. steed and uncoated), gsm coated). sm) coated. Paper Size: 7.2 x 5.7"/182 x heet top tray, 3,000-sheet stack tray of 5.8 er with a 500-sheet top tray and 2,000-she to 13 x 19.2"/330 x 488mm up to 350 gsm ets/90 gsm coated). er, Crease and Two-Sided Trimmer. 10 gsm. Compatibility: Production Ready 48 mm) to 13 x 19.2" (330 x 488 mm). Max 22"/330 x 488 mm. tain or valley creases per sheet.			
Optional Finishing	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-pother; 5.5 x 8.5 in. / A5 output to top tray; pubond to 110 lb. cover / 60 to 256 gsm (coatec Business Ready Finisher Booklet Maker Fil (single position stapling or dual or 4-position s 200 sets (single-position staple) 8.5 x 11 in. / A Other; 5.5 x 8.5 in. / A5 output to top tray; pun Stacker Tray-16 lb. bond to 110 lb. cover / 60 tc (coated and uncoated). Booklet Maker-Saddle Production Ready Finisher (requires Interl 146mm to 11.7 x 17"/297 x 432mm. Max Wei 5.75"/148 x 146mm to 13 x 19.2"/330 x 488m Production Ready Finisher Plus (requires I stacker tray. Used to connect third-party inlir Production Ready Finisher with Booklet M Trays: 500-sheet top tray, 2.000-sheet stacking. Xerox® SquareFold® Trimmer Module: Fact Xerox® C/Z Folder: Sheet Size: 8.5 x 11" (A4). Finisher, Booklet Maker. Xerox® Inserter: Capacity: 250 sheets. Capa Weight: 350 gsm. Compatibility: Production Max Weight: 350 gsm. Compat	osition staple) 8.5 x 11 in. / A4. Sizes: Stanch and offset. Paper weights: Top Tray land uncoated). Inisher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A 4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in., ch and offset. Paper weights: Top Tray-14 256 gsm (coated and uncoated). Booklet stitch 2 to 16 sheets (7 sheets at 106 to 1 ace Decurler Module): Booklet Size: 100 ght: 350 gsm. Options: Punch, Inserter arm. Interface Decurler Module): Provides sa ite finishing options. Includes PFIM Partne aker (requires Interface Decurler Moduray, saddle-stitch booklet tray (up to 120 er Trim: 120 pages (30 sheets). Compatibil Half-Z Fold Sheet Size: Larger stocks reduced in the state of the	d. Stacking Stapling Tray: 3,000 sheets uncking; 4 x 6 in. to 12 x 19.2 in. / A6 to SRA3, S-16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 1 5 lb. bond to 110 lb. cover / 60 to 350 gsm (co. Maker-16 lb. bond to 110 lb. cover / 60 to 256 76 gsm coated or 5 sheets at 177 to 220 gsm 0 sheets (90 gsm) uncoated, 35 sheets (90 gsm) dc //Z Folder. Trays: Two output trays, 500-s me function as the Production Ready Finisher Finishing Interface Module. ule): Booklet Size: 7.17 x 10.1*/182 x 257mm 0 pages, 30 sheets/90 gsm uncoated, 25 sheelity: Production Ready Finisher, Booklet Makeucing to 8.5 x 11" (A4). Weight Range: 64 - 90 pling, stacking. Paper Size: 7.2 x 5.8" (182 x 1 aper Size: 7.7 x 8.3*/194 x 210 mm to 13 x 19 uffering Unit: Up to five customizable mountabilities: Face trimming, square fold, rotate	istapled or 100 sets (dual or 4-position stap tapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to. (coated and uncoated). Stacker Tray-16 lb. 1 Tray: 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. sted and uncoated), gsm coated). sm) coated. Paper Size: 7.2 x 5.7"/182 x heet top tray, 3,000-sheet stack tray of 5.8 er with a 500-sheet top tray and 2,000-she to 13 x 19.2"/330 x 488mm up to 350 gsm. ets/90 gsm coated). er, Crease and Two-Sided Trimmer. 0 gsm. Compatibility: Production Ready 48 mm) to 13 x 19.2" (330 x 488 mm). Max 22"/330 x 488 mm. tain or valley creases per sheet.			
erox App Gallery	11x17 in., 8.5 x 14 in., A3 or 200 sets (single-p Other; 5.5 x 8.5 in. / A5 output to top tray; pu bond to 110 lb. cover / 60 to 256 gsm (coatec Business Ready Finisher Booklet Maker Fii (single position stapling or dual or 4-position s 200 sets (single-position staple) 8.5 x 11 in. / A Other; 5.5 x 8.5 in. / A5 output to top tray; pun Stacker Tray-16 lb. bond to 110 lb. cover / 60 to (coated and uncoated). Booklet Maker-Saddle Production Ready Finisher (requires Interl 146mm to 11.7 x 17"/297 x 432mm. Max Wei 5.75"/148 x 146mm to 13 x 19.2"/330 x 488m Production Ready Finisher Plus (requires I stacker tray. Used to connect third-party inlir Production Ready Finisher with Booklet M Trays: 500-sheet top tray, 2,000-sheet stacking. Xerox® SquareFold® Trimmer Module: Facc Xerox® C/Z Folder: Sheet Size: 8.5 x 11" (A4) Finisher, Booklet Maker. Xerox® Inserter: Capacity: 250 sheets. Capa Weight: 350 gsm. Compatibility: Production R Max Weight: 350 gsm. Compatibility: Production Plockmatic Pro 50/35 Booklet Maker: Bo	osition staple) 8.5 x 11 in. / A4. Sizes: Stanch and offset. Paper weights: Top Tray Land uncoated). sisher: Offsetting Top Tray: 500-sheets taple) or 100 stapled sets of 11 x 17 in. / A 4. Sizes: Stacking; 4 x 6 in. to 12 x 19.2 in., ch and offset. Paper weights: Top Tray-16. 256 gsm (coated and uncoated). Booklet stitch 2 to 16 sheets (7 sheets at 106 to 1 ace Decurler Module): Booklet Size: 106 ght: 350 gsm. Options: Punch, Inserter arm. nterface Decurler Module): Provides sa le finishing options. Includes PFIM Partne aker (requires Interface Decurler Moduray, saddle-stitch booklet tray (up to 120 et Trim: 120 pages (30 sheets). Compatibil Half-Z Fold Sheet Size: Larger stocks rediscibilities: Trimming, punching, folding, sta Ready Finisher. linge: 0.236" (6 mm) to 0.985" (25 mm). Pution Ready Finisher and Booklet Maker. Bellet Capacity: 200 pages (50 sheets). Cap Max Weight: 300 gsm. Compatibility: Prod	d. Stacking Stapling Tray: 3,000 sheets uncking; 4 x 6 in, to 12 x 19.2 in. / A6 to SRA3, S -16 lb. bond to 110 lb. cover / 60 to 350 gsm 8.5 x 11 in. / A4 unstapled. Stacking Stapling 3 / SRA3. 11x17 in., 8.5 x 14 in., A3 or / A6 to SRA3. Stapling; 7.25 x 10.5 in. to 11 x 1 fb. bond to 110 lb. cover / 60 to 350 gsm (cor. Maker-16 lb. bond to 110 lb. cover / 60 to 256 76 gsm coated or 5 sheets at 177 to 220 gsm of the core of the cor	stapled or 100 sets (dual or 4-position startapling; 7.25 x 10.5 in. to 11 x 17 in. / B5 to (coated and uncoated). Stacker Tray-16 lb. 1 Tray: 1,500 sheets unstapled or 200 sets 7 in. / B5 to A3. steed and uncoated), gsm coated), sim) coated. Paper Size: 7.2 x 5.7*/182 x heet top tray, 3,000-sheet stack tray of 5.i er with a 500-sheet top tray and 2,000-she to 13 x 19.2*/330 x 488mm up to 350 gsm ets/90 gsm coated). er, Crease and Two-Sided Trimmer. 2 gsm. Compatibility: Production Ready 48 mm) to 13 x 19.2* (330 x 488 mm). Mos 2*/330 x 488 mm. tain or valley creases per sheet. crease and bleed trim.			



Configurations vary by geographical location.

