

# HP Latex 630 W Printer

Embrace new possibilities with an unbeatable white ink printing experience<sup>1</sup>—easily.



## POSSIBILITIES—The best white ink print experience<sup>1</sup>

- Do more in your shop with the easiest white ink printer<sup>1</sup> that adapts to your business needs.
- Produce a wide range of signage and décor jobs including applications with thin film and papers.
- Deliver stunning prints with vivid colors, smooth gradients, and sharp text at 150 ft<sup>2</sup>/hr.<sup>2</sup>

## EFFORTLESS—Get it done quickly and easily

- Find peace of mind with automatic maintenance processes and user-replaceable printheads.
- Save space and time with fast and automated frontloading system.
- Easily reprint projects with job storage in the printer up to 10 GB.
- Monitor your printer from anywhere and expand your capabilities with the cloud-based HP PrintOS app.

## GO BEYOND—Lead with environmental certifications<sup>3</sup>

- Contribute to a comfortable<sup>4</sup> working environment with water-based HP Latex Ink technology.
- Differentiate your business with environmental certifications<sup>3</sup>—including UL ECOLOGO<sup>®5</sup> and EPEAT<sup>6</sup>.
- Reduce your plastics consumption with carton-based cartridge<sup>7</sup> and labelless supplies; free recycling via HP Planet Partners.<sup>8</sup>

This printer is intended to work only with cartridges that have a new or reused HP chip, and it uses dynamic security measures to block cartridges using a non-HP chip. Periodic firmware updates will maintain the effectiveness of these measures and block cartridges that previously worked. A reused HP chip enables the use of reused, remanufactured, and refilled cartridges. More at: <http://www.hp.com/learn/ds>

<sup>1</sup> Easiest/best white ink experience due to transparent ink maintenance with Automatic Ink Recirculation System between the HP Latex 832 Ink Mix and HP 832 White Latex Ink Cartridge. This ensures white ink is constantly circulating and doesn't settle. It's easy to remove the white printhead from the carriage and store it in an offline rotation chamber when not printing with white ink. This avoids unnecessary white ink waste and prevents the white printhead from getting clogged because of its dense white ink chemistry. All white printmodes are available at different white ink densities to get different levels of opacity (spot, underflood, overflood, and 3-layer—up to 260% white ink density).

<sup>2</sup> Standard mode (Generic SAV Calendar) 6-pass, 6 colors, 110% ink density. Based on internal HP testing on MACTAC JT 8500 WG-PG. Print speed may vary due to the adaptive printing mechanism, which is designed to avoid image quality defects.

<sup>3</sup> Based on internal competitive analysis with public information. Applicable to HP Latex technology compared to competitive large format printing alternatives using solvent and UV technologies. See individual product data sheets for more information at <http://hp.com/go/latex>

<sup>4</sup> Based on odor sensory evaluation when printing with the HP Latex 630 series printer and Mimaki UJV 100-160. Tests done in a 57 sqm room with 5ACH. Test conducted by Odournet following the standard VDI3882, where the HP Latex 630 series air quality were characterized, when Printing, as "neutral" for hedonic tone compared to the Mimaki UJC 100-160.

<sup>5</sup> UL ECOLOGO<sup>®</sup> Certified HP 832 Latex inks meet a range of stringent human health and environmental considerations. For certifications, see <http://www.ul.com/EL> and <http://www.ul.com/gg>

<sup>6</sup> Applicable to select HP Latex printers. EPEAT registered where applicable/supported. See <http://epeat.net> for registration status by country.

<sup>7</sup> Applicable to HP 832. Plastic reduction based on moving from plastic ink cartridge to cardboard ink cartridges, with annual manufacturing saving of 33 tons of plastic based on average units of HP 831 and HP 831A ink cartridges from 2018 to 2020.

<sup>8</sup> Visit <http://hp.com/recycle> to see how to participate and for HP Planet Partners program availability; program may not be available in your jurisdiction. Where this program is not available, and for other consumables not included in the program, consult your local waste authorities on appropriate disposal.

Technical specifications

Print	
Printing modes	35 m²/hr - Max Speed (2-pass) 18 m²/hr - Speed (4-pass) 14 m²/hr - Standard (6-pass) 11 m²/hr - Quality (8-pass) 8 m²/hr - High Saturation (12-pass) 7 m²/hr - Standard for Backlits and Textiles (14-pass) 6 m²/hr - White Spot (100%) 3 m²/hr - White Overflow (100%) 2 m²/hr - White Underflood (100%) 1 m²/hr - 3 Layers (160%) <sup>1</sup>
Print resolution	Up to 1200 x 1200 dpi
Ink types	Water-based HP Latex Inks
Ink cartridges	9 (black, cyan, light cyan, light magenta, magenta, yellow, white, HP Latex Optimizer, HP Latex Overcoat)
Cartridge size	1 L
Printheads	6 (1 cyan/black, 1 magenta/yellow, 1 light cyan/light magenta, 1 white, 1 HP Latex Optimizer, 1 HP Latex Overcoat)
Long-term print-to-print repeatability	95% of colors < 3 dE2000 <sup>2</sup>
Media	
Handling	Roll feed, take-up reel, automatic horizontal cutter (for vinyl, banner and canvas <sup>3</sup> , paper-based media, and film)
Media types	Banners, self-adhesive vinyls, films, papers, wallcoverings, canvas, synthetics, (fabrics, mesh, textiles, and any other porous materials require a liner)
Roll size	457 to 1625-mm rolls (580 to 1625-mm rolls with full support)
Maximum roll weight	42 kg
Maximum roll diameter	250 mm
Thickness	Up to 0.5 mm
Applications	Banners, Customizable clothing, Displays, Exhibition and event graphics, Exterior signage, Floor graphics, Indoor posters, Interior decoration, Labels and stickers, Light boxes - film, Light boxes - paper, POP/POS, Posters, Vehicle graphics, Wall decals, Window graphics
Connectivity	
Interfaces	Gigabit Ethernet (1000Base-T)
Dimensions (W x D x H)	
Printer	2603 x 844 x 1405 mm
Shipping	2800 x 1130 x 1271 mm
Operating area	2793 x 2100 mm
Weight	
Printer	236 kg
Shipping	353 kg
What's in the box	HP Latex 630 W Printer, printheads, maintenance cartridge, printer stand, take-up reel, user maintenance kit, edge holders, quick reference guide, HP Sai Flexi RIP Basic Software, documentation software, power cords, air purgers, 2-in spindle adaptor
Environmental ranges	
Operating temperature	15 to 30°C
Operating humidity	20 to 80% RH (non-condensing)
Acoustics	
Sound pressure	55 dB(A) (operating), 38 dB(A) (idle), <20 dB(A) (sleep)
Sound power	7.5 B(A) (operating), 5.5 B(A) (idle), <4 B(A) (sleep)
Power	
Consumption	0.9-2.0 kW (2.9 kW peak) (printing), 60 W (ready), <4.5 W <sup>4</sup> (sleep) (<15 W <sup>5</sup> with DFE)
Requirements	Input voltage (auto ranging) 200-240 V (±10%) two wires and PE; 50/60 Hz (±3 Hz); two power cords; 5 A max printer power cord, 12 A max curing power cord
Certification	
Safety	IEC 62368-1 2nd and 3rd ed and IEC 60950-1+A1+A2 compliant;; USA and Canada (CSA listed); EU (LVD, EN 60950-1 and EN 62368-1 compliant); China (CCC)
Electromagnetic	Compliant with Class A requirements, including: USA (FCC rules), Canada (ICES), EU (EMC Directive), Australia and New Zealand (RCM), Japan (VCCI), Korea (KCC), China (CCC)
Environmental	ENERGY STAR®; RoHS (WEEE, EU, EAEU, China, Korea, India, Ukraine, Turkey); REACH; EPEAT; OSHA; CE marking compliant
Warranty	One-year limited hardware warranty

Ordering information

Product	
171K6A	HP Latex 630 W Printer
Accessories	
171K8A	HP Latex 630 Output Platen Protector Accessory
21V10A	HP Latex 600/700/800 User Maintenance Kit
421S3A	HP Latex Media Feed Accessory
7HR19A	HP Latex 630/700/800 Media Loading Accessory
Original HP printing supplies	
4UU93A	HP 836 White Latex Printhead
4UU94A	HP 836 Optimizer Latex Printhead
4UV29A	HP 832 1-liter White Latex Ink Cartridge
4UV75A	HP 832 1-liter Black Latex Ink Cartridge
4UV76A	HP 832 1-liter Cyan Latex Ink Cartridge
4UV77A	HP 832 1-liter Magenta Latex Ink Cartridge
4UV78A	HP 832 1-liter Yellow Latex Ink Cartridge
4UV79A	HP 832 1-liter Light Cyan Latex Ink Cartridge
4UV80A	HP 832 1-liter Light Magenta Latex Ink Cartridge
4UV81A	HP 832 1-liter Optimizer Latex Ink Cartridge
4UV82A	HP 832 1-liter Overcoat Latex Ink Cartridge
4UV83A	HP 832 Ink Mix Container
4UV95A	HP 836 Black/Cyan Latex Printhead
4UV96A	HP 836 Magenta/Yellow Latex Printhead
4UV97A	HP 836 Light Cyan/Light Magenta Latex Printhead
4UV98A	HP 836 Overcoat Latex Printhead
Original HP large format printing materials	
HP Recycled <sup>6</sup> Removable Adhesive Fabric, 3-in Core (Latex/solvent): REACH compliant <sup>7</sup> HP Recycled <sup>8</sup> Satin Canvas, 3-in Core (Latex/solvent): REACH compliant <sup>7</sup> HP Premium Poster Paper: FSC® certified <sup>9</sup> HP PVC-free <sup>10</sup> Wall Paper: UL GREENGUARD GOLD Certified <sup>11</sup> , FSC® certified <sup>9</sup> , meets AgBB criteria <sup>12</sup> HP Permanent Gloss Adhesive Vinyl: REACH compliant <sup>7</sup> HP Prime Gloss Air GP: REACH compliant <sup>7</sup>	
For the entire HP Large Format Printing Materials portfolio, please see HPLFMedia.com.	
Service and Support	
U67E7E HP 2 year Plus Service Plan Hardware Support w/DMR U67E8E HP 3 year Plus Service Plan Hardware Support w/DMR U67F0E HP 5 year Plus Service Plan Hardware Support w/DMR U67F1PE HP 1 year Post Warranty Plus Service Plan Hardware Support w/DMR U67F2PE HP 2 year Post Warranty Plus Service Plan Hardware Support w/DMR	

<sup>1</sup> Print speeds may vary due to the adaptive printing mechanism to avoid image quality defects. Print mode names may vary depending on the media or application.

<sup>2</sup> The color variation between printed jobs has been measured at 12 pass mode on vinyl media. Reflective measurements on a 943 color target under CIE standard illuminant D50, and according to the standard CIEDE2000 as per CIE Draft Standard DS 014-6/E:2012. 5% of colors may experience variations above 3 dE2000. Backlit substrates measured in transmission mode may yield different results.

<sup>3</sup> Automatic horizontal cutter is for use with thinner banners and canvas only. It is recommended to perform a test.

<sup>4</sup> Excluding Type 2 DFE (Digital Front End) as defined in Energy Star® Product Specification for Imaging Equipment version 3.1.

<sup>5</sup> Total power measured in sleep mode including the Digital Front End contained on the product.

<sup>6</sup> Product consists of PET fabric and coatings. With liner attached, 72% by weight of the product consists of recycled content. Base material fabric is made from 100% recycled resin.

<sup>7</sup> As of the date of this document, this product does not contain any of the chemicals on the EU's Candidate List for Authorization (otherwise known as Substances of Very High Concern) in concentrations exceeding 0.1%. To determine the status of SVHC in HP products, see the HP REACH Article 33 Declaration published at HP Printing Products and Consumable Supplies.

<sup>8</sup> 62% by weight of the product consists of recycled content. Base material fabric is made from 100% recycled resin. Certified according to Global Recycled Standard (GRS) Version 3.0, March 2017.

<sup>9</sup> Trademark license code FSC-C115319.

<sup>10</sup> Chemical analysis demonstrated elemental chlorine to be below 200 ppm. Presence of chlorine is attributed to residual chlorine used in the papermaking process, and not due to the presence of PVC.

<sup>11</sup> HP PVC-free Wall Paper printed with HP Latex Inks is UL GREENGUARD GOLD Certified. UL GREENGUARD GOLD Certification to UL 2818 demonstrates that products are certified to UL's GREENGUARD standards for low chemical emissions into indoor air during product usage. For more information, visit <http://ul.com/gg>

<sup>12</sup> With HP Latex Inks, prints meet AgBB criteria for health-related evaluation of VOC emissions. See <http://umweltbundesamt.de/en/topics/health/commissions-working-groups/committee-for-health-related-evaluation-of-building>

